

Product Specification: pH Meter (S058)

PHT810 pH-Meter with automatic pH Calibration

electrode sold separately

Product Description

- Handy and robust
- Current value memory
- Fully automatic pH-calibration
- Approx. 5 years battery life
- Simple calibration with keypad
- Electrodes for different applications



For use with: Food industry, industrial water, waste water, rinsing water in washer-disinfectors, laboratories, pools & aquariums

Technical data

Measuring range	0 pH...14 pH
Accuracy	± 0.03 pH
Resolution	0.01 pH
Operating Temperature	0 °C...+50 °C
Storage temperature	-25 °C...+60 °C
Battery	Lithium 3V/1Ah
Battery lifetime	approx. 5 years
Dimensions	110 x 54 x 22 mm
Weight	approx. 200 g
Certificate	Supplied with Certificate of conformance, UKAS or Caltrac calibration available

This document was prepared on behalf of Klipspringer Ltd and the information included is to the best of our knowledge correct at the time of writing. Klipspringer offers the information within this document as a guide only, they do not represent any guarantee of the prescribed products in the sense of the legal guarantee regulations. It is the responsibility of the end user to ensure the items purchased are suitable for the intended application.

Supplier/Importer: Klipspringer Ltd
Address: Rynor House, Farthing Road, Ipswich, Suffolk, UK. IP1 5AP
Telephone: 0044 (0) 1473 461800
Email/Website: info@klipspringer.com / www.klipspringer.com

Sheena Britton
 Technical Compliance Manager
 Klipspringer Ltd



20-03-17

Date of issue	20-03-17	Revision No.	001	Revised by	SB
Authorised by	S. Britton	Document No.	S058	Page 1 of 1	